



## Z22P250XGEE

Rigid Light/Medium Duty Caster with Zinc Plated Steel and 5" Gray on Gray Soft Rubber Wheel.

---

**Related Product:** WC2054GS

**Related Product:** xxxxxxxxxxxxxx

## ADDITIONAL INFORMATION

|                            |  |
|----------------------------|--|
| <b>Caster Type</b>         | Rigid  |
| <b>Wheel Part No</b>       | 5-281M-GG  |
| <b>Wheel Material</b>      | Soft Rubber  |
| <b>Attachment Method</b>   | Top Plate  |
| <b>Caster Finish</b>       | Zinc Plated Steel with Lacquer Dip   |
| <b>Product Series</b>      | 20   |
| <b>Series Types</b>        | 20-Light/Medium Duty   |
| <b>Industry</b>            | Food/Beverage, Hospitality, Institutional, Janitorial, Retail Environment          |
| <b>Application</b>         | Food Service, Institutional, Material Handling, Retail, Stocking, Waste Containers |
| <b>Threadguard</b>         | YES  |
| <b>Imperial Plate Size</b> | 3 1/8" x 4 1/8"  |
| <b>Overall Height</b>      | 6"   |
| <b>Plate Hole Centers</b>  | 2 1/16" x 3 1/8"   |
| <b>Swivel Radius</b>       | 4"   |
| <b>Weight</b>              | 2  |
| <b>Wheel Diameter</b>      | 5"   |
| <b>Wheel Tread Width</b>   | 1 3/8"   |

|                          |                |
|--------------------------|----------------|
| <b>Wheel Color</b>       | Gray/Gray      |
| <b>Axle Size</b>         | 5/16"          |
| <b>Bearing Type</b>      | Dual Precision |
| <b>Bearing Material</b>  | Steel          |
| <b>Wheel Profile</b>     | Flat           |
| <b>Hub Width</b>         | 1 3/5"         |
| <b>Wheel Durometer</b>   | A60            |
| <b>Load Capacity</b>     | 300 LBS        |
| <b>Operating Temp</b>    | -30°F TO 140°F |
| <b>Bearing Size</b>      | 5/16"          |
| <b>Warranty Duration</b> | 1 year         |