



The #1 supplier of shopping cart wheels and casters in the U.S.

CLEANMASTER

MBC-3-A65

Recycleable, Non-rusting Commercial Mop Bucket Caster and Wheel



The P&H **CLEANMASTER** mop bucket caster is manufactured from environmentally friendly materials that make it recycleable, while maintaining its superior non-rusting properties. This caster features a raceway design that minimizes vibration during operation to help keep water from splashing over the edges of the bucket.

This chemically resistant caster is designed to perform in wet or potentially corrosive environments.

- 1 - Nylon cap is interlocked with caster stem to prevent pull-out
- 2 - Vertical journal bearing design
- 3 - 5/32 metal balls are cleaned and lubricated by the nylon and delrin raceways to prevent rust
- 4 - Nylon-6 30% glass filled yoke maximizes tensile strength
- 5 - High density Thermoplastic Rubber wheel

FEATURES

Wheel

Standard model wheel is soft, gray, high quality TPR tread
High impact black polypropylene hub

Also available in economical hard D65 Gray polypropylene with black polypropylene hub and plain bore bearing

Yoke

High impact plastic eliminates rust
Durable nylon w/ 30% glass fiber
Grade 5 Dacromet coating kingpin
Rust resistant Dacromet coated axle & nut

Bearing

Vertical Journal bearing
Smooth operation with minimal vibration
Sealed bearing raceway prevents corrosion
Anti-rust bearing shaft



CASTER

MBC-3-A65

Attachment	7/16" socket
Overall Height	5 7/8"
Bore	13/16"
Wheel Diameter	3"
Load Capacity	125 lbs.
Weight	.83 lbs.
Hardness (durometer)	A65
Finish	Nylon-6 30% glass filled yoke

APPLICATIONS

Replacement casters designed specifically to fit commercial and industrial portable mop buckets. Precision engineering ensures smooth and quiet gliding. Unified bayonet stem simplifies installation.

This caster is rust free and durable for wet environments where steel casters fail due to rust from moisture. Features an integrated design requiring no assembly.

WHEEL

Hardness (durometer)	A65
Diameter	3"
Weight	.36 lbs.
Tread Width	13/16"
Load Capacity	125 lbs.
Hub Width	1.35"
Bore	3/8"
Wheel Bearing	Plain
Temperature Range	-20° F to 120° F



800 354 8622
orders@phcasters.com
www.phcasters.com

