

1.800.354.8622

www.phcasters.com



We Keep
THE WORLD ROLLING

NEW PRODUCT

SERIES 50




HEAVYHAUL




Z50P3828PUL


| | |
|---------------------|---|
| Plate Size | 4" x 4 1/2" |
| Bolt Hole Spacing | 2 5/8" x 3 5/8" slotted to 3" x 3" |
| Attaching Bolt Size | 3/8" |
| Overall Size | 4 1/2" x 6 1/4" |
| Bolt Hole Spacing | 2 7/16" x 4 15/16" slotted to 3 3/8" x 5 1/4" |
| Bolt Size | 1/2" |

- Caster:** Heavy duty swivel or rigid caster
- Finish:** Zinc plated steel w laquer dipped yoke
- Bearing:** 1/2" Dual precision bearing
- Wheel:** 8" x 2" Die cast TPU red wheel on aluminum hub
- Mount:** 4" x 4 1/2" x 1/4" steel plate
- Axle:** 1/2" Diameter with lock nut

| |  |  |  |
|--------------------------|---|---|--|
| SWIVEL P/N | Z40P382CLPL | Z50P382YRPL | Z50P3828PUL |
| RIGID P/N | Z42P382CLPL | Z52P382YRPL | Z52P3828PUL |
| Load Capacity | 1,000 lbs | 1,200 lbs | 1,500 lbs |
| Mount Height | 9.5" | 9.5" | 9.5" |
| Max Tow Speed | 2.2 mph | 5 mph | 6.5 mph |
| Bearing Type | Dual precision | Dual precision | Dual precision |
| Swivel Type | Double ball race | Precision bearing | Precision bearing |
| Operating Temp Range | -40 to 165 F | -40 to 180 F | -40 to 185 F |
| Most common applications | Manual pull carts, material handling, client interface carts, retail stores, distribution centers | Amusement parks, mix of towed and manual pull material handling, economic tow alternative | Heavy industrial, automotive facilities, tow lines, tug carts, AGV's, fragile load hauling |

WE PROVIDE PRODUCTS FOR

 **RETAIL**
Shopping carts, garment racks, backroom, bakery, deli, storage.

 **MATERIAL HANDLING**
Loading dock, warehouse, home improvement, nursery.

 **INSTITUTIONAL**
Hospitality, food service, healthcare, universities, office.

 **INDUSTRIAL**
Factory, backroom, conveyor, ladders, automotive, construction.

- ## OPTIONS
- CAM LOCK BRAKE
 - PRECISION BEARING
 - 4 POSITION SWIVEL LOCK
 - TOP LOCK BRAKE
 - HEAVY DUTY TOP LOCK BRAKE

FOR MORE INFORMATION

1601 W. Harris Rd., Arlington, Texas - 76001,
Phone: 1.800.354.8622 | Fax: 817.468.2850
Email: sales@phcasters.com



#phcasters @phcasters