



The #1 supplier of shopping cart wheels and casters in the U.S.

SANDWICH

W320CHW0K

Shock and Vibration Absorbing Wheel



P&H's metric line includes the **SANDWICH** wheel, also called shock absorbing wheels. These wheels absorb vibration to protect delicate loads and minimize instability on uneven surfaces.

A unique blend of rebound rubber sandwiched between two layers of nylon, the Sandwich wheel offers the strength and durability of nylon wheels and the shock absorbing and sound dampening qualities of rebound rubber.

These features are particularly important in roll-on/roll-off applications.

WHEEL

W320CHW0K

Part No.	W320CHW0K	W320DHW0K	W320CHWNK	W320DHWNK
Diameter	100 mm	125 mm	100 mm	125 mm
Tread Width	35 mm	35 mm	35 mm	35 mm
Hub Width	40 mm	40 mm	40 mm	40 mm
Weight	.23 kgs.	.27 kgs.	.23 kgs.	.27 kgs.
Capacity	200 kgs.	200 kgs.	200 kgs.	200 kgs.
Hardness	D75	D75	D75	D75
Bolt Axle	M8	M8	M8	M8
Bearing	Precision	Precision	Roller	Roller
Threadguard	None	None	None	None

APPLICATIONS

- Airports
- Electronics distribution
- Automotive
- Engineering
- Hospital/Medical
- Roll-on/roll-off
- Fragile/sensitive equipment
- Dollies
- Roll cages




W320CHW0K

2-3/8" x 3-5/8" Plate



X80M4DH3W0X5

FEATURES



- 1 - Two layers of nylon sandwich a layer of high elasticity rubber
- 2 - Precision or roller bearing

Wheel

- Available in 100 and 125 mm diameters
- Two layers of nylon sandwich a layer of high elasticity rubber
- Minimizes instability on uneven surfaces

Caster

- Available in zinc plated steel or 304 stainless steel
- Swivel or rigid plate attachments
- Available with total lock brake

Bearing

- Precision or roller style bearing
- Anti-rust coating

OPTIONS



X81M4CH3W0X5



Part No.	Model/Swivel Offset	Wheel Size	Tread Width	Load Capacity	Material
X80M4CH3W0X5	Swivel/37mm	100 mm	35 mm	200 kgs.	Zinc plated steel w lacquer dip
X81M4CH3W0X5	Rigid	100 mm	35 mm	200 kgs.	Zinc plated steel w lacquer dip
X80M4CH3W0X5L	Total Lock (swivel 37mm)	100 mm	35 mm	200 kgs.	Zinc plated steel w lacquer dip
X80M4DH3W0X5	Swivel/37mm	125 mm	35 mm	200 kgs.	Zinc plated steel w lacquer dip
X81M4DH3W0X5	Rigid	125 mm	35 mm	200 kgs.	Zinc plated steel w lacquer dip
X80M4DH3W0X5L	Total Lock (swivel 37mm)	125 mm	35 mm	200 kgs.	Zinc plated steel w lacquer dip



800 354 8622
 orders@phcasters.com
 www.phcasters.com

