

WI3054GDW

SERIES 30

Flatspot Resistant Shopping Cart Wheel



P&HCASTERS



Features

- Special compound tread resists flatspotting
- Dual Precision Bearing
- Mechanical bond prevents tread squeak and separation
- Wheels perform best when installed on the rear of the shopping cart in pairs
- HDPE threadguards
- Exceptional maneuverability and soft ride
- High impact polypropylene hub
- Installs like a standard shopping cart wheel

Applications

Shopping Carts



Technical

The P&H Super Friction wheels combine the best of two of P&H's top line products resulting in a wheel that is the most flat spot resistant wheel available.

Made from a unique natural rubber compound developed by P&H to be extremely abrasion resistant and have a high degree of surface grip, our SuperWheels deliver a superior user experience combined with exceptional durability. These wheels outperform standard shopping cart wheels and carry our "2 Years of Confidence" Product Warranty.

Wheel Material	Soft Rubber on Polypropylene
Wheel Color	Gray/Gray
Wheel Diameter	5"
Bearing Type	Dual Precision
Tread Width	1 1/4"
Axle Size	5/16"
Load Capacity	250 Lbs,
Hub Width	1.598"
Threadguard	Yes
Operating Temperature	-30°F TO 140°F
Wheel Hardness	Shore A80
Warranty	2 Years

Options

Product No.	Diameter	Bearing Type	Tread Width	Load Capacity	Color/Material	Brake
Z30C154IGDEFR	5"	Dual Precision	1 1/4"	250 Lbs.	Gray/Gray Soft Rubber	No



For more information about P&H Casters products contact:

P&H Casters Company, Inc. 1016 W. Harris Rd. Arlington, Texas, USA

Tel +1 800 354 8622 Fax +1 817 468 2850 Email: sales@phcasters.com

We Keep Your World Rolling