

WI20DH234

SERIES 20

Premium Soft Rubber Material Handling Wheel

P&HCASTERS
WE KEEP YOUR WORLD ROLLING



Features

- Available in 100 and 125 mm diameter
- Easy rolling, cushioned tread
- Shock absorbing
- High tensile strength/ Low rolling resistance
- More durable than polypropylene
- Maintenance free
- HDPE threadguards
- NSF Certified



Applications

Tow Lines | Assembly Lines | Automotive Distribution | Engineering | Hospital/Medical Machine Shop | Dollies | Roll Cages

Technical

Wheel Material	Soft Rubber
Wheel Color	Blue/Black
Wheel Diameter	125mm
Bearing Type	Precision with anti-rust coating
Tread Width	35mm
Axle Size	10mm
Load Capacity	440 LBS
Hub Width	45mm
Threadguard	YES
Bearing Size	12-17mm
Wheel Hardness	Shore A70
Operating Temperature	-30°F TO 140°F
Warranty	1 Year

P&H's metric products include this premium material handling wheel that performs exceptionally well for operations such as conveyor tow lines where wheels run continuously. These wheels combine the load bearing qualities found in steel with an exceptional level of resistance to most chemicals, high tensile strength, low rolling resistance and non-marking tread. Stronger than polypropylene, these wheels have an excellent level of resilience.

Yokes to complete caster assembly are available in both swivel and rigid models and a total lock brake model.

Caster Option

Product No.	Caster Type	Bearing	Tread Width	Load Capacity	Color/Material	Brake
X84M4DHI200	Swivel	12-17mm Precision	35mm	440 lbs.	Blue/Black	No



For more information about P&H Casters products contact:
P&H Casters Company, Inc. 1016 W. Harris Rd. Arlington, Texas, USA
Tel +1 800 354 8622 Fax +1 817 468 2850 Email: sales@phcasters.com

Products that make sense.